



LEICA GEOVID HD-B 42 EDITION 2017

Technical data



Rangefinder	Leica Geovid 8x42 HD-B EDITION 2017 (Typ 402)	Leica Geovid 10x42 HD-B EDITION 2017 (Typ 403)
Order no.	40 072	40 073
Package includes	contoured neoprene carrying strap "sport", front lens caps, eyepiece caps, battery, Cordura case	contoured neoprene carrying strap "sport", front lens caps, eyepiece caps, battery, Cordura case
Magnification	8 x	10 x
Front lens diameter	42 mm	42 mm
Exit pupil	5.2 mm	4.2 mm
Twilight factor	18.3	20.5
Field of view at 1,000 yds/m	426 ft / 130 m	374 ft / 114 m
Close focus range	approx. 16.5 ft / 5.0 m	approx. 16.5 ft / 5.0 m
Diopter compensation	± 4 dpt	± 4 dpt
Distance measurement:		
Range	10 yds to approx. 2,200 yds / 10 m to approx. 2,000 m	10 yds to approx. 2,200 yds / 10 m to approx. 2,000 m
Equivalent horizontal range (EHR)	10 yds to 1,200 yds / 10 m to 1,100 m	10 yds to 1,200 yds / 10 m to 1,100 m
Measuring accuracy	± 1 yd / m to 547 yds / 500 m ± 2 yds / m to 1,094 yds / 1,000 m ± 0,5 % beyond 1,094 yds / 1,000 m	± 1 yd / m to 547 yds / 500 m ± 2 yds / m to 1,094 yds / 1,000 m ± 0,5 % beyond 1,094 yds / 1,000 m
Display	LED display with 4 characters and ambient-light-controlled brightness	LED display with 4 characters and ambient-light-controlled brightness
Eyecup with twist-and-pull action	yes, detachable, with 4 click-stops	yes, detachable, with 4 click-stops
Eyepieces for eyeglass wearers	yes	yes
Focusing	internal focusing with center focusing barrel	internal focusing with center focusing barrel
Prism system	Perger Porro-System	Perger Porro-System
Coating	HDC® multicoating, AquaDura® lens coating	HDC® multicoating, AquaDura® lens coating
Waterproof	waterproof to 16.5 ft / 5 m	waterproof to 16.5 ft / 5 m
Body	magnesium, nitrogen-filled	magnesium, nitrogen-filled
Dimensions (W x H x D)	4.9 x 7.0 x 2.8 in / 125 x 178 x 70 mm	4.9 x 7.0 x 2.8 in / 125 x 178 x 70 mm
Weight	approx. 34.3 oz / 975 g incl. battery	approx. 33.3 oz / 980 g incl. battery
Yard/Meter switch	yes	yes
Laser	eye-safe, invisible light laser compliant with EN and FDA Class 1	eye-safe, invisible light laser compliant with EN and FDA Class 1
Measuring mode	scan mode, single measurement	scan mode, single measurement
Ballistic functions	Equivalent horizontal range (EHR), point of aim correction, number of clicks required on elevation turret	Equivalent horizontal range (EHR), point of aim correction, number of clicks required on elevation turret
Bullet trajectories	12 fixed pre-installed curves Integration of custom data using microSD card	12 fixed pre-installed curves Integration of custom data using microSD card
Power supply	1 x 3 V/ CR2 lithium button cell	1 x 3 V/ CR2 lithium button cell
Battery life	approx. 2,000 measurements at 68° F / 20°C	approx. 2,000 measurements at 68° F / 20°C
Accessories	tripod adapter (42 220) floating carrying strap (42 163)	tripod adapter (42 220) floating carrying strap (42 163)