TECHNICAL SPECIFICATIONS

LEICA ZM 1 AND LEICA ZM 2

Diameter	41 mm
Movement type	Leica caliber ZM 1 and ZM 2, hand-winding
Jewels	26 jewels
Frequency	28.800 A/h, 4 Hz
Power reserve	60 hours
Classic function	Hours, minutes and small second display
Complications	1) Push-crown; 2) mode indicator; 3) date display; 4) quick date setting; 5) power reserve indicator; LEICA ZM 2 only: 6) second time zone (GMT) function; 7) day/night indicator
Special features	Patented push-crown to enter the time setting mode, with seconds reset function and setting mode indication. Power reserve indicator with 2 gradually closing blades. Quick date setting with pusher. LEICA ZM 2 only: GMT inner ring with hour alignment and synchronised day and night display
Case	Stainless steel (316L) Total height 14.5 mm, total length 48 mm Finishing with highly polished and satin surfaces, bevelled edges
Water resistance	50 m 5 ATM (ISO 2281 standard)
Front glass	Domed sapphire crystal glass, anti-reflective coating on both sides, scratch-resistant coating, screw-mounted bezel
Case bottom glass	Flat sapphire crystal glass, anti-reflective coating on both sides, scratch-resistant coating, screw-mounted
Dial and hands	Dial in high-strength aluminum, milled from the full; with rhodium-plated and diamond cut indices, watch hands and small second decor ring
Strap	Calf leather, black with matching stitching, red brand stitching, and red backlining; Genuine Alligator leather, matte black with matching stitching, red brand stitching, and red backlining
Buckle	Leica pin buckle, stainless steel, milled, polished and brushed finishing, with LEICA engraving