



## TECHNICAL SPECIFICATIONS

### LEICA ZM 11

<b>Calibre</b>	Leica LA-3001 in collaboration with Chronode SA, Switzerland
<b>Movement type</b>	Mechanical Automatic, self-winding
<b>Jewels</b>	35 jewels
<b>Frequency</b>	28'800 A/h, 4 Hz
<b>Power reserve</b>	Approximately 60 hours
<b>Precision</b>	-4/+6 seconds per day, measured in 5 positions
<b>Classic function</b>	Hours, minutes and center seconds
<b>Complications</b>	Date with quick set function
<b>Special feature</b>	Easy-Change System (strap change)
<b>Material</b>	316L Stainless Steel or Titanium Grade 5
<b>Case diameter</b>	41mm
<b>Thickness</b>	13mm
<b>Weight</b>	Stainless steel case 78g   Titanium case 61g
<b>Water-resistance</b>	100m   10ATM (ISO 2281 standard)
<b>Crown</b>	Screw down crown, with quick date change and time-setting mode
<b>Dial</b>	Dual-layered dial with inner bezel and printed minute track
<b>Front glass</b>	Double-domed sapphire crystal, with hardened anti-reflective coating on both sides
<b>Case-back glass</b>	Single domed sapphire crystal, with inside-laser-print
<b>Hands and Indices</b>	Indices and hands filed with Swiss Grade A Super-LumiNova
<b>Bands</b>	Vulcanized rubber strap   Cordura fabric strap Integrated 316L stainless steel or titanium grade 5 bracelet
<b>Buckle</b>	Rubber and textile straps: Leica tang buckle with logo engraving, in stainless steel 316L or titanium grade 5 Metal bracelets: Butterfly Clasp with 2 pushers in stainless steel 316L or titanium grade 5
<b>Warranty</b>	5-year International Warranty