



# LEICA ZM 12

## Technical Specifications

Caliber	Leica LA-3002 in collaboration with Chronode SA, Switzerland
Movement type	Mechanical automatic, self-winding
Jewels	38 jewels
Frequency	28,800 A/h, 4 Hz
Power reserve	Approximately 60 hours
Precision	-4/+6 seconds per day, measured in 5 positions
Classic function	Hours, minutes, and small second at 6 o'clock
Complications	none
Special feature	Easy-Change System (strap change)
Material	316L stainless steel or grade 5 titanium
Case diameter	39 mm
Thickness	13 mm
Weight	Stainless-steel case: 66 g   Titanium case: 52 g
Water resistance	100 m   10 ATM (ISO 2281 standard)
Crown	Screw-down crown, with time-setting mode
Dial	Dual-layered dial with inner bezel and printed minute track
Front glass	Double-domed sapphire crystal, with hardened anti-reflective coating on both sides
Case-back glass	Single-domed sapphire crystal, with inside laser print
Hands and indices	Indices and hands filled with Swiss Grade A Super-LumiNova
Bands	Vulcanized rubber straps   Fabric straps Integrated 316L stainless-steel or grade 5 titanium bracelet
Buckle	Rubber and textile straps: Leica tang buckle with logo engraving, in 316L stainless steel or grade 5 titanium Metal bracelets: Butterfly clasp with 2 pushers in 316L stainless steel or grade 5 titanium
Warranty	5-year international warranty