



Installation instructions for the Leica TL2 - Firmware 1.4

Dear Customers,

by installing the firmware 1.4 on your Leica TL2 you will gain additional functions and performance for your camera.

Update Contents

Model	LEICA TL2
Update Version	Version 1.4
Update File Name	TL2_1400.LFU

Description

Version	Description
1.4	<p><u>Performance Improvements:</u></p> <ul style="list-style-type: none">➤ NEW MENU ITEM: Selection of LCD / Viewfinder settings The content appearing on screen and in the viewfinder are identical. Now the user can determine when and where the content appears.➤ NEW MENU ITEM: Left Dial Customizable functions Touching the left function display brings up the available function tiles. These functions are now customizable. The user can choose 6 out of 13 functions➤ NEW MENU ITEM: More options for Top FN Button The user can now assign 1 of 6 functions to the FN button on top of the camera.➤ NEW MENU ITEM: Electronic Shutter options The user can now choose the electronic shutter to be off, permanently on or extended to the mechanical shutter.➤ Focus Peaking in AF Mode In AF mode the user can always take manual focus corrective action by using the MF ring. With FW 1.4 focus peaking is available during this operation➤ Focus Peaking for M-/R-Lenses While using M-/R-lenses via M-Adapter L focus peaking is now available➤ EV adjustment during video recording During video recording the EV value can be adjusted via the left top dial➤ Enable zoom-in while playback in EVF Viewing images in playback in EVF user can zoom-in with right top dial

- Enable zooming during rating function
During single image rating function the zoom-in /zoom-out function via right top dial is available now
- Video: more options for video resolution
4K 30fps, FHD 30fps, FHD 60fps, HD 60fps, Slomo 120fps
- Improvement of Color Aberration for all TL lenses
- Improvement of the AFc precision and AF speed

Firmware Update Procedure

1. Download an updated version of the firmware.
2. Copy the firmware file onto a SD Memory Card in its top level folder.
3. Make sure to turn off the power switch on the camera.
4. Insert the fully charged battery to the body. If the battery is not fully charged, the update process screen will not appear.
5. Insert the SD Memory Card into the camera.
6. Turn the camera – while simultaneously pressing the video release button – on.
7. The firmware update screen will appear. Press OK.
8. The LEICA TL2 will start the update process. The firmware update will take about 90 seconds.
9. After the update process please restart the camera.

CAUTION:

Please do **not** turn off your camera, or do **not** remove the SD Memory Card, do **not** remove the lens while updating your camera's firmware. **DOING SO CAN CAUSE A SERIOUS DAMAGE TO YOUR CAMERA!**