



LEICA ULTRAVID HD-PLUS EDITION SAFARI

Technical data



Binocular	Leica Ultravid 8 x 32 HD-PLUS Edition Safari	Leica Ultravid 10 x 32 HD-PLUS Edition Safari
Order No.	40 665	40 666
Delivery scope	Eyepiece caps, case "Aneas for Leica", 2 leather carrying straps	Eyepiece caps, case "Aneas for Leica", 2 leather carrying straps
Magnification	8 x	10 x
Front lens diameter	32 mm	32 mm
Exit pupil	4 mm	3.2 mm
Twilight factor	16	17.9
Field of view at 1,000 m at 1,000 yds	135 m 404 ft	118 m 352 ft
Eye-relief	13.3 mm	13.2 mm
Objective angle of view	7.7°	6.7°
Close focusing distance	approx. 2.1 m / 7.2 ft	approx. 2 m / 6.6 ft
Diopter compensation	± 4 diopters	± 4 diopters
Automatic diopter compensation ADC™	yes	yes
Eyepieces for eyeglass wearers	yes, removable, with 4 click stops	yes, removable, with 4 click stops
Adjustable interpupillary distance	52 – 74 mm	52 – 74 mm
Focusing	internal focusing via central focusing device	internal focusing via central focusing device
Prism system	roof prism with phase correcting coating P40 and HighLux-System HLS™	roof prism with phase correcting coating P40 and HighLux-System HLS™
Coating	HDC®-Plus multicoating and Leica AquaDura® lens coating	HDC®-Plus multicoating and Leica AquaDura® lens coating
Watertightness	to a depth of 5 m / 16.5 ft	to a depth of 5 m / 16.5 ft
Housing	magnesium, nitrogen-filled	magnesium, nitrogen-filled
Dimensions (W x H x D)	116 x 116 x 56 mm 4.57 x 4.57 x 2.2 in	116 120 x 56 mm 4.57 x 4.7 x 2.2 in
Weight	approx. 650 g / 22.9 oz	approx. 650 g / 22.9 oz
Order No. Accessories		
Neoprene carrying strap, contoured	42 052 (Pitch black), 42 053 (Chocolate brown) 42 054 (Juicy orange), 42 055 (Racing green)	42 052 (Pitch black), 42 053 (Chocolate brown) 42 054 (Juicy orange), 42 055 (Racing green)
Floating carrying strap, orange	42 163	42 163
Tripod adapter	42 220	42 220





LEICA ULTRAVID HD-PLUS EDITION SAFARI

Technical data



Binocular	Leica Ultravid 8x42 HD-PLUS Edition Safari	Leica Ultravid 10x42 HD-PLUS Edition Safari
Order No.	40 667	40 668
Delivery scope	Eyepiece caps, case "Aneas for Leica", 2 leather carrying straps	Eyepiece caps, case "Aneas for Leica", 2 leather carrying straps
Magnification	8 x	10 x
Front lens diameter	42 mm	42 mm
Exit pupil	5.2 mm	4.2 mm
Twilight factor	18.3	20.5
Field of view at 1,000 m at 1,000 yds	130 m 389 ft	112 m 336 ft
Eye-relief	15.5 mm	16 mm
Objective angle of view	7.4°	6.4°
Close focusing distance	approx. 3 m/9.8 ft	approx. 2.9 m/9.5 ft
Diopter compensation	± 4 diopters	± 4 diopters
Automatic diopter compensation ADC™	yes	yes
Eyepieces for eyeglass wearers	yes, removable, with 4 click stops	yes, removable, with 4 click stops
Adjustable interpupillary distance	55 – 75 mm	55 – 75 mm
Focusing	Internal focusing via central focusing device	Internal focusing via central focusing device
Prism system	roof prism with phase correcting coating P40 and HighLux-System HLS™	roof prism with phase correcting coating P40 and HighLux-System HLS™
Coating	HDC®-Plus multicoating and Leica AquaDura® lens coating	HDC®-Plus multicoating and Leica AquaDura® lens coating
Watertightness	to a depth of 5 m/ 16.5 ft	to a depth of 5 m/ 16.5 ft
Housing	magnesium, nitrogen-filled	magnesium, nitrogen-filled
Dimensions (W x H x D)	121 x 142 x 67 mm 4.8 x 5.6 x 2.6 in	120 x 147 x 68 mm 4.7 x 5.8 x 2.7 in
Weight	approx. 790 g / 27.9 oz	approx. 790 g / 27.9 oz
Order No. Accessories		
Neoprene carrying strap, contoured	42 052 (Pitch black), 42 053 (Chocolate brown) 42 054 (Juicy orange), 42 055 (Racing green)	42 052 (Pitch black), 42 053 (Chocolate brown) 42 054 (Juicy orange), 42 055 (Racing green)
Floating carrying strap, orange	42 163	42 163
Tripod adapter	42 220	42 220

