



LEICA TEMPUS 2

Technical Data.



| Designation | Leica Tempus 2 ASPH. 2.5 MoA |
|------------------------------------|--|
| Device type | Reflex sight |
| Order no. | 55 503 without mount / 55 501 with mount (Picatinny) |
| Scope of delivery | protection cover, lens cleaning cloth, battery compartment opener, battery, hexagonal key (1.5 mm) two Torx mounting screws (T10), EAW mount (55 501 only) |
| Front lens (aspherical) | 21 x 25 mm |
| Parallax free | 40 m |
| Mounting option | Docter Sight |
| Adjustment point impact | 1.1 MoA per click (approx. 1.6 cm at 50 m) |
| Adjustment range reticle | 100x100 MoA (approx. 1.5 m at 50 m) |
| Reticle (red-dot) | 2.5 MoA (approx. 3.6 cm at 50 m) |
| Reticle (red-dot) intensity levels | 12 levels |
| Automatic switch-off | after 4 hours when with motion sensor off / after 3 minutes without movement with motion sensor on |
| Powering on | per +/- button |
| Shooting resistance | 1.000 g (1 ms) |
| Waterproof | 3 ft. / 1 m depth, 10 minutes |
| Battery | 1 x 3 V CR 2032 |
| Dimensions (L x H x D) | 2.11 x 1.38 x 1.13 in / 53,6 x 35 x 28,6 mm |
| Weight | 1.76 oz / 50 g |

